

07560 Membrane Roofing/Roof Coating



TPO Primer A140
Primer for NEW TPO

**PRODUCT
DESCRIPTION**

TPO Primer A140 is a solvent based primer designed for new TPO. It is a fast-drying primer that provides strong adhesion on new TPO surfaces. A140 also resists ponding water, providing additional protection on your roof.

BENEFITS

- Adhesion to New TPO
- Fast Drying Time

INSTALLATION

- All surfaces to be primed must be clean and dry. It may be necessary to power wash surfaces to enhance adhesion.
- May be brushed, rolled, or spray applied. If spray applied, low-pressure airless spray equipment should be used.
- Apply A140 at a rate of .33 gallons per 100 square feet. A140 should be applied in only one coat.
- A140 should not be applied when it is raining or when the threat of rain is imminent. This product contains flammable solvents and is intended for use by professional contractors only.
- Adhesion tests should always be performed to ensure suitability of use.
- **For best results, thoroughly blend contents of all containers using a power mixer for a minimum of 10 minutes prior to use.**
- For application details see specific Installation Guide Specifications.

STORAGE

A140 should be stored between 50° and 80° Fahrenheit. Shelf life is 12 months in sealed, properly stored containers.

PACKAGING SIZES

TPO Primer A140 is available in 5 gallon pails and 55 gallon drums.

WARRANTY

Various warranties are available for specific National Coatings Roofing Systems installed by approved applicators.

MAINTENANCE

Periodic maintenance of Roofing Systems ensures extended performance and reduces life cycle costs.

TECHNICAL SERVICES

Additional information, product brochures, and guide specifications are available. Roof energy evaluations, life cycle cost analyses, and other roof management services are available.





07560 Membrane Roofing/Roof Coating

TPO Primer A140

Physical Properties

Property	Results
Appearance	Transparent Charcoal
Specific Gravity @25°C	0.88
Clean Up	Mineral Spirits
Recordable VOC	<250g/L
Solids Content by Weight	11% +/-2%
Tack-Free Time	0.5-1 hour 12 months
Cure Time	1 -2 hours

These products are for industrial/commercial applications only. Suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use are beyond our control.

Contact National Coatings Corporation for more detailed specifications and where to purchase TPO Primer A140



Revision Date: June 12, 2020