



At SpeedLine, we're proud to offer the Ingenico Lane/3000 PIN pad, which is the latest advancement in EMV card processing technology. Whether you are using the older iPP320 or some other form of EMV hardware, here is what you can expect from the Lane/3000.

Versatile Payment Options: With the Lane/3000, you can accept payment using EMV chip and magstripe, EMV chip and PIN, contactless NFC, mobile wallet, and even more.

Advanced PCI Compliance: Not only is the Lane/3000 PCI PTS 5.x certified, but it is also designed to provide long-term encryption capabilities and is P2PE certified when using Worldpay Express. With the latest peer-to-peer encryption technology designed to ensure long-term compliance, the Lane/3000 is virtually future-proof.

Fast Checkout: The Lane/3000 is equipped with an optimized smartcard reader and contactless card reader zone that displays the order total. This means faster customer checkout times and better service.

	Ingenico Lane/3000	Ingenico iPP320 (Previous Model)
Processor	Cortex A5, 64 bits	ARM 9, ARM 7
Memory	256 MB Flash, 128 MB RAM	128 MB Flash, 32 MB SDRAM, µSD up to 8G
OS Requirements	Windows 7 or higher Must be a supported SpeedLine OS	Windows 7 or higher Must be a supported SpeedLine OS
Store Environment Requirements	1 available USB port	1 available USB port
SpeedLine Version Requirements	7.3 Release 300 and later	7.2 and later
Card Readers	Magstripe, Smart card, Contactless	Magstripe, Smart card, Contactless
Display (Non-Touch)	Colour, QVGA (320 x 240 pixels) 2.8" backlight	Black and White, LCD (128 x 64 pixels) White backlight
Terminal Connectivity	Wired	Wired
Terminal Connections	USB-to-serial connection	USB-to-serial connection
Terminal Size	3.26" x 7.08" x 1.69"	3.26" x 6.61" x 1.57"
Weight	8.89 oz	9.41 oz
Environment	Operating temperature: 32 to 122 Storage temperature: -4 to 131 Relative humidity: 85% HR at 104	Operating temperature: 32 to 113 Storage temperature: -4 to 131 Relative humidity: 85% HR at 131
Accessories	PCI compliant privacy shield (optional, factory mounted)	PCI compliant privacy shield (optional)
Security	PCI PTS 5.x certified Active connector removal Kensington lock receptacles	PCI PTS 4.x certified
Warranty Options	3 year 1-day air advanced exchange. No charge for any repairs or re-injections, OR 1-year depot warranty. 8-12 week repair time. The customer pays for shipping and re-injections	1-year limited warranty based on the vendor invoice date to SpeedLine.