9320 S SERIES IR CAMERA



The ICI S Series IR Camera offers unmatched image sensitivity and accuracy in a 320 x 240 radiometric imager. With less than 2 in³ in overall dimension the camera fits in the tightest of areas. The ICI S Series operates on less than 1.1 W of power, via a USB Mini-B to USB 2.0, providing real time radiometric data streamed directly to any desktop, laptop, tablet or embedded system. Windows and Linux software, drivers and SDK are available for any and all custom applications. Includes IR Flash version 1.0 Software.

Features

- · Unmatched image sensitivity
- · Multi-device linking
- · Radiometric data streaming
- Integrates into embedded systems
- Windows and Linux software
- Small size
- · Light weight
- Low power < 1.1 W by USB
- Drivers and SDK available

• Detector Array: UFPA (VOx)

Specifications

- Pixel Pitch: 17 µm
- FOV: lens dependent
- Measurement Distance: lens dependent
- Pixel Resolution: 320 x 240
- Spectral Band: 7 μm to 14 μm
- Thermal Sensitivity (NETD):
- < (20 mK) 0.02 °C at 30 °C (86 °F)
- Frame Rate: 9 Hz
- Dynamic Range: 14-bit
- Temperature Range: 25 °C 45 °C (77°F to 113 °F)
- Operation Range: 0 °C to 50 °C (32 °F to 122 °F)
- Storage Range: -40 °C to 80 °C (-40 °F to 176 °F)
- Humidity: 5% to 95% non-condensing
- Accuracy: ± 0.2 °C (0.36 °F)
- Pixel Operability: > 99 %
- Shock/Vibration: 70 G/4.3 G
- Dimensions (without lens):
- 37 mm x 37 mm x 41.5 mm (L x W x D ± 0.5 mm) (1.46" x 1.46" x 1.63" (L x W x H ± 0.02"))
- Power: 5 V DC 500 mA, < 1.1 W
- Weight (without lens): 47 g (1.66 oz)
- Interface: USB Mini-B
- Video: raw data
- Emissivity Correction: 0.01 to 1.0
- IP Rating: IP 54
- Built-in shutter
- · Aluminum enclosure

Options/Lenses

Applications

• Skin temperature measurement

· Hospital healthcare procedures

Sub-acute healthcare settings

Healthcare roboticsRadiometric imaging

Scientific researchBreast imaging

Airport screening

- Optional: 1/4"-20 tripod
- Temperature reference source
- 8 mm Manual focus lens (40° x 30° FOV, +50 g (+1.76 oz))
- 12.5 mm Manual focus lens (25° x 18.8° FOV, +64 g (+2.26 oz))



9320 S Series IR Camera

THIS DEVICE IS INTENDED FOR ADJUNCTIVE USE WITH OTHER CLINICAL DIAGNOSTIC PROCEDURES TO MEASURE HUMAN BODY TEMPERATURE VIA NON-CONTACT SKIN MEASUREMENTS VISUALIZED FROM THE HUMAN FACE. NOT MEANT FOR STANDALONE CLINICAL DIAGNOSTIC PROCEDURES OR TO TREAT OR DIAGNOSE PATIENTS.

ICI cameras fall under US Federal Law and Export Control.

Specifications subject to change without notice.