

# UNIVERSAL WALL MOUNT BRACKET

Our Universal Wall Mount Bracket's hollow, curved design provides cable management, weather protection, and is made of thickened rust-resistant aluminum. It is built-to-last in outdoor conditions; also suitable for indoor use. Easily adjustable with a 45-degree pan and 180-degree tilt. Can be installed on walls or ceilings. The J Bracket can accommodate most 1/4-20" infrared cameras, both small and large, as well as our thermal reference source devices. Useful for medical screening, building security, and home installation.

## Features

---

- Pan 45°
- Tilt 180°
- Adjustable length
- High loading capacity
- Durable and sturdy
- Heavy duty, rust-resistant aluminum alloy construction
- Cable management through pole
- Compatible with ICI's 1/4-20" cameras
- Indoor/Outdoor use

## Specifications

---

- **Maximum Load:** 22 lbs
- **Swivel Angle:** 180°
- **Camera Mount:** 1/4-20"
- **Material:** Aluminum
- **Dimensions:** 280 mm x 160 mm x 87 mm (L x W x H ± 0.5 mm)
- **Diameter:** 37 mm ± 0.5 mm
- **Wall Thickness:** 1.5 mm

## Applications

---

- 8000/9000 series cameras
- FM series cameras
- FMX series cameras
- Mirage series cameras
- Temperature reference sources
- Swir series cameras
- Corona 640
- TDLAS



Universal Wall Mount Bracket

ICI cameras fall under US Federal Law and Export Control.