



Huskie's S-Series tools cut anything from guy wire\* to anchor rod and most overhead and underground cables. The S-series cutters are portable, lightweight, and made to last years under the toughest field conditions. The S-40B and S-85 feature a two stage pumping piston for rapid advance.

The new S-240CC, S-32CC and SP-24CC hydraulic cutters were specially engineered to cut the toughest EHS guy wire, ground and anchor rods. The SP-24CC is the remote head version, which requires an external 10,000 psi pump in order to operate. The anvil style, center cut blades eliminate jamming problems common to shear style cutters, and the blades are easily replaced in the field. The tools are made of high grade steel and have rubber handle grips. All tools are black zinc oxide coated to help reduce corrosion. A flip-top latch opens the tool jaw to easily accept cables and wires. The head can be rotated up to 180° to facilitate easy wire positioning and operator leverage.

Consult the chart below to pick the proper cutter for your needs. If there are any questions about capacities, or special applications please contact Huskie Tools.

\*NOTE: DO NOT CUT EHS GUY WIRE. FOR EHS GUY WIRE SPECIFY S-240CC, S-32CC OR THE REMOTE HEADS SP-24CC OR SP-32CC1.



S-16



S-20



S-32

Specifications									
Model	S-16	S-20	S-240	S-32	S-40B	S-35	S-85	S-240CC	S-32CC
Output	4.4 ton	4.4 ton	7.8 ton	19.8 ton	6.3 ton	13 ton	2.7 ton	7.8 ton	19.8 ton
Weight	6 lbs	6 lbs	9 lbs	21 lbs	12 lbs	17 lbs	15 lbs	11 lbs	23 lbs
Length	15" L	15" L	17" L	27" L	23" L	24" L	26" L	18.5" L	27" L
Jaw Opening	.6"	.75"	.9"	1.25"	1.6"	2"	3.3"	.9"	1.25"
Capacities									
Wire Ropes	16 mm 5/8"	20 mm 3/4"	22 mm 7/8"	32 mm 1-1/4"	20 mm 3/4"	26 mm 1"	Do Not Cut	Do Not Cut	Do Not Cut
Soft Steel Bolts	16 mm 5/8"	17 mm 11-16"	22 mm 7/8"	32 mm 1-1/4"	20 mm 3/4"	32 mm 1-1/4"	Do Not Cut	16 mm 5/8"	26 mm 1"
Rebar, Ground & Anchor Rod	13 mm 1/2"	13 mm 1/2"	16 mm 5/8"	22 mm 7/8"	16 mm 5/8"	20 mm 3/4"	Do Not Cut	16 mm 5/8"	26 mm 1"
Cu & Al Wire	16 mm 5/8"	20 mm 3/4"	22 mm 7/8"	32 mm 1-1/4"	40 mm 1-1/2"	50 mm 2"	76 mm 3"	Do Not Cut	Do Not Cut
ACSR	16 mm 5/8"	20 mm 3/4"	22 mm 7/8"	32 mm 1-1/4"	40 mm 1-1/2"	50 mm 2"	Do Not Cut	Do Not Cut	Do Not Cut
Standard Guy Wire	13 mm 1/2"	14 mm 1/2"	16 mm 5/8"	22 mm 7/8"	16 mm 5/8"	20 mm 3/4"	Do Not Cut	14 mm 1/2"	22 mm 7/8"
Telephone & Lead Sheathed Cable	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	85 mm 3.35"	Do Not Cut	Do Not Cut
Chain	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	Do Not Cut	1/4"	1/2"