



Tri-Flex®  
3-part braided wire rope sling

Features:

- Provides the best combination of strength and flexibility
- Heavy gauge stainless steel tag made in accordance with ASME B30.9 & API RP2C
- 6x19 class IWRC EIP bright wire rope supplied standard on 1/4" – 1-1/8"
- 6x37 class IWRC EIP bright wire rope supplied standard on 1-1/4" and larger
- D/d of the eye equals 2 to 1
- D/d of the body equals 5 to 1
- Proof testing available upon request
- Design factor 5 to 1

How to order:

- Specify part number and length

Composed of 3 parts of EIP Rope	Part Number	Actual Finished Diameter	Rated Capacities in Short Tons			Weight per foot. Lbs.
			Vertical	Choker	Vertical Basket	
1/4"	13010103	1/2"	1.7	1.3	3.4	.44
5/16"	13010104	5/8"	2.6	1.9	5.2	.68
3/8"	13010105	3/4"	3.6	2.7	7.2	.99
7/16"	13010106	7/8"	4.9	3.7	9.8	1.33
1/2"	13010107	1"	6.4	4.8	12.8	1.75
9/16"	13010108	1-1/8"	8.0	6.0	16.0	2.24
5/8"	13010109	1-1/4"	9.9	7.4	19.8	2.73
3/4"	13010110	1-1/2"	14.0	10.5	28.0	3.9
7/8"	13010111	1-3/4"	19.0	14.3	38.0	5.4
1"	13010112	2"	24.8	18.6	49.6	7.0
1-1/8"	13010113	2-1/4"	31.2	23.4	62.4	8.9
1-1/4"	13010114	2-1/2"	38.4	28.8	76.8	10.0
1-3/8"	13010115	2-3/4"	46.0	34.5	92.0	13.3
1-1/2"	13010116	3"	55.0	41.2	110.0	15.8
1-3/4"	13010118	3-1/2"	73.0	54.8	146.0	21.5
2"	13010120	4"	95.0	71.2	190.0	28.0
2-1/4"	13010122	4-1/2"	118.0	88.5	236.0	35.6
2-1/2"	13010124	5"	145.0	109.0	290.0	44.0

Note:

- Specify wire rope construction, grade, and finish if other than standard
- US Patent # 5,561,973



Follow OSHA, ASME B30.9 and Manufacturer's Guidelines. Can fail if damaged, misused, or overloaded. Inspect before use. Use only if trained. Do not exceed rated capacity. Protect from contact with edges. DEATH or INJURY can occur from improper use or maintenance.