

Light Champion Double Sheave Snatch Blocks

- Light champion snatch block as a double sheave block.
- Drop forged swivel hook or swivel shackle.
- Can be furnished with bronze bushings or roller bearings.
- Opening feature permits easy insertion of wire rope in both sheaves with removal of one bolt.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- 4-1/2" - 10" models furnished with dual rated wireline sheaves.
- Fatigue Rated.
- All sizes are RFID Equipped.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26



408



409



Sheave Diameter (in.)	Bearing Code	Stock No.		Wire Rope Size (in.)	Working Load Limit (t)	Weight Each (lbs.)	
		408 with Hook	409 with Shackle			408 with Hook	409 with Shackle
4-1/2	BB	104023	105022	3/8 - 1/2	4	18	18
6	BB	104103	105102	5/8 - 3/4	12	45	50
6	RB	104121	105120	5/8 - 3/4	12	45	50
8	BB	104185	105184	5/8 - 3/4	12	53	58
8	RB	104201	105200	5/8 - 3/4	12	53	58
10	BB	104265	105264	5/8 - 3/4	12	70	75
10	RB	104283	105282	5/8 - 3/4	12	70	75
12	BB	194578	195185	5/8	12	90	95
12	RB	168044	195229	5/8	12	90	95
12	BB	104345	105344	3/4	12	90	95
12	RB	104363	105362	3/4	12	90	95
14	BB	194621	195247	5/8	12	100	105
14	RB	194649	195265	5/8	12	100	105
14	BB	104425	105424	3/4	12	100	105
14	RB	104443	105442	3/4	12	100	105

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size.