

Fatigue Rated

70 SERIES BLOCKS
Also available with
Rod Hook Clevis



McKissick® Oilfield Tubing Blocks utilizing new Split Nut Retention System. Revolutionary new retention system eliminates conventional threaded nut and potential problems associated with thread corrosion.

- Exclusive E-Z opening guards, no bolts to pull out and lose. Feature gives fastest possible exposure of sheave cluster for quick reeving.
- Extremely short overall length, extra weight, excellent balance for fast non-wobbling falls.
- Extra large sealed sheave bearing diameters for fully rated capacities.
- Roller thrust bearing in hook.
- Duplex hook for easy elevator operation, locks in eight positions.
- Convenient rod hook clevis available.
- Completely streamlined, no projections.
- McKissick Roll-Forged, flame hardened sheaves, grooved for proper wire line size. Contact Crosby for additional wire line sizes.
- McKissick Split-Nut® hook parts precision machined and individually fitted for maximum performance.
- All blocks available with additional cheek weights.
- Can be manufactured to API-8C specifications when requested at time of order.
- All sizes are RFID EQUIPPED.



Licensed Under
API Spec 8C-0021



70 Series Tubing Blocks

The 70 Series has a spring loaded hook that is better for heavy usage and larger depths. Tends to last longer since the shock loads are somewhat absorbed.

Stock No.	Block Config.*	Rod Hook Clevis Working Load Limit (lbs.)	Working Load Limit (Tons)	Wire Line Size (in.)	Weight Each (lbs.)
111792	20" 73	25,000	75	7/8	1770
111890	20" 73-A**	25,000	75	7/8	1815
111818	24" 73	40,000	100	1	2634
111916	24" 73-A**	40,000	100	1	2750
111827	30" 73	45,000	150	1-1/8	4450
111925	30" 73-A**	45,000	150	1-1/8	4068
128793	30" 74	45,000	150	1-1/8	4400
125545	30" 74-A**	45,000	150	1-1/8	4462

* Spring loaded duplex hook assuring ample travel for efficient tubing operations. No load carrying threads
** A = Rod Hook Clevis attachment standard.

80 Series Tubing Blocks

The 80 Series has no spring loaded hook and is better for shallow depths and rework.

80 SERIES BLOCKS
Also available with
Rod Hook Clevis



Stock No.	Block Config.	Rod Hook Clevis Working Load Limit (lbs.)	Working Load Limit (Tons)	Wire Line Size (in.)	Weight Each (lbs.)
112130	17" 83	15,000	50	7/8	1082
112238	17" 83-A**	15,000	50	7/8	1110
112149	20" 82	15,000	50	7/8	1125
112247	20" 82-A**	15,000	50	7/8	1243
112158	20" 83	25,000	75	7/8	1603
112256	20" 83-A**	25,000	75	7/8	1659
112167	24" 82	25,000	75	1	1800
112265	24" 82-A**	25,000	75	1	1830
112176	24" 83	40,000	100	1	2200
112274	24" 83-A**	40,000	100	1	2185
117475	24" 84	40,000	100	1	2700
117484	24" 84-A**	40,000	100	1	2750
112185	30" 83	45,000	150	1-1/8	2700
112283	30" 83-A**	45,000	150	1-1/8	3564
117493	30" 84	45,000	150	1-1/8	3850
117509	30" 84-A**	45,000	150	1-1/8	4130

** A = Rod Hook Clevis attachment standard.