

475



Well Logger's Blocks

- Alloy aluminum housing for maximum strength and minimum weight.
- Conductor cable ONLY is recommended for use with Well Logger's Blocks.
- For use in high speed well logging, perforating, etc.
- Extra large double row, pre-adjusted sealed tapered bearing.
- Quick opening pin for fast string-up, light weight for easy handling.

477



475 / 477 Floor Blocks

Sheave Diam. (in.)	Block No.	Floor Block Stock No.	Working Load Limit (Tons)*	Conductor Cable Size (in.)†	Weight Each (lbs.)	Connection
7	475	180020	1-1/2	3/16	10	Swivel Hanger
10	475	180128	1-1/2	3/16	11	Swivel Hanger
10	475	180253	2-1/2	5/16	21	Swivel Hanger
12	475	180440	2-1/2	5/16	24	Swivel Hanger
14	475	180618	2-1/2	5/16	43	Swivel Hanger
14	477	169784	6	1/4	58	Swivel Clevis
20	477	191072	6	1/4	70	Swivel Clevis
24	477	191107	10	5/16	130	Swivel Clevis

* Ultimate Load is 4 times the Working Load Limit.

† Other cable sizes available upon request.

476



476 Top Blocks

Sheave Diam. (in.)	Block No.	Floor Block Stock No.	Working Load Limit (Tons)*	Conductor Cable Size (in.)	Weight Each (lbs.)	Connection
7	476	180075	2-1/2	3/16	10	Stinger Pin
10	476	180333	4	5/16	21	Stinger Pin
12	476	180529	4	5/16	24	Stinger Pin
14	476	180707	4	5/16	43	Stinger Pin

* Ultimate Load is 4 times the Working Load Limit.

731



Crown Blocks

- McKissick Roll-Forged™ sheaves with flame hardened grooves.
- Double row pre-adjusted sealed tapered bearings mounted on a steel shaft.
- Heavy center and side plates for proper support of center pin.
- Pre-assembled units for rapid attachment to crown assembly for installation on derrick.
- On multiple sheave assemblies, one sheave can be grooved for sand line on request.
- Other sizes available upon request.
- Sheaves manufactured to API-8C specifications.

Sheave Diam. (in.)	Block No.	Crown Block Stock No.	No. of Sheaves	Working Load Limit (Tons)	Standard Wire Rope Size (in.)*	Weight Each (lbs.)
24	241	351158	1	15	7/8	200
24	242	351167	2	30	7/8	278
24	243	351176	3	45	7/8	375
24	731	351185	1	35	1	200
24	732	351194	2	75	1	350
24	733	351201	3	100	1	525
24	734	351210	4	125	1	720
30	741	351229	1	40	1-1/8	325
30	742	351238	2	80	1-1/8	560
30	743	351247	3	110	1-1/8	800
30	744	351256	4	140	1-1/8	982
30	745	351265	5	170	1-1/8	1163

* May be furnished in other wire rope sizes.