

SPECS

3 MIN

Change Over

20 CASES

Speed Per Minute

ANY SIZE

Forms nearly any size case or tray

PACKAGE TYPES

Cases, Trays, and RRP

[View Full Specs ▲](#)

KEY FEATURE	Ergonomic Low Magazine
KEY FEATURE	Quick Changeover, Light Tooling
LAYOUT	Right Hand/Left Hand Counter Flow or Through-Flow
SYSTEM PLC	Allen-Bradley Compact Logix
SYSTEM HMI	Allen-Bradley Panelview 700 or 1000
SERVO MOTORS	Allen-Bradley VPL or VPF (food grade)
SAFETY SYSTEM	Category II or III
ENCLOSURE PANEL	NEMA 12 (Painted), NEMA 4 (SS) or NEMA 4X(SS)
ENCLOSURE	Voltage Separation Standard (High/Low)

PANEL COOLING	Vortex, Heat Exchanger or Air-Conditioner
UTILITIES - POWER	480v 60hz 3ph
UTILITIES - AIR	15 SCFM @ 80PSIG
WEIGHT	2,700 lbs
LENGTH	15' 0" (4,570 mm)
WIDTH	3' 7" (1,120 mm)
HEIGHT	8' 3" (2,515 mm)
FRAME MATERIALS	Stainless Steel or Painted Carbon Steel
MAGAZINE	Extended Magazine Length
STATUS GLOW	Bright Internal LED Status Lights