

75F® Products, Applications, and Services

PRODUCTS



Central Control Unit

- A wireless, state-of-the-art building sensor and control supervisor
- Instantly compatible BACnet IP server
- Intuitive mobile pairing, configuration, and settings setup




Smart Node

- Terminal equipment controller with 11 interface ports for nearly any equipment type or brand
- Automatic, wireless upgrades and pre-written sequences of operation



Smart Stat

- Commercial thermostat & humidistat for IAQM and thermostatic control
- Reads temperature, humidity, CO2, VOC, light, sound, supply air temperature, and occupancy



Smart Damper

- Proactively modulate a few degrees at a time throughout the day
- Available in round and rectangular versions, with inline or external actuators



Wall Sensor

- Reads temperature and humidity
- Proprietary 1-wire protocol to communicate with master device



Wireless Wall Sensor

- Reads temperature and humidity
- Tangle-free sensor with a more than five-year battery life



Local Interface Sensor

- Reads temperature, humidity and light
- Can communicate with SN, HIA or LPI via 4 wire interface



Duct Sensor

- Reads temperature and humidity
- 4 side venting holes on pipe and variable pipe length



Flush Sensor

- Reads temperature and humidity
- Easily mounted with self-drilling screws



Ceiling Sensor

- Reads temperature and humidity
- Easily mounted on the ceiling by a threaded bush, adjustable with screw