

Specifications

POWERCAT

Communications Controller module

Communications interfaces supporting 2w, 4w, V.23, FFSK, VF radio, Data radio, Ethernet TCP/IP, Fibre Optic
4 individually isolated ports supplied standard with one serial card (RS232 or RS485)

Protocol support for DNP3/IP, DNP3 Master, DNP3 Slave, Modbus Master, Modbus Slave, HDLC, HDLC/IP, Conitel 2020/2025

Time Synchronisation IRIG-B, 1pps -UTC and standard offsets.

Config port - RS232 for Local Master or local Aspxex HMI

Security inputs - Tamper and Inhibit, Relay Alarm Output

LED display for individual port operation

Digital Input Module

40 voltage driven digital inputs isolated in pairs, common negative for each pair. Inversion, denounce, floating or latching selectable.

Input range
1/2/24VDC or 110/120VDC selectable -48Vneg available on request.

Isolation
Opto-coupler

Digital Output Module

40 pulsed or continuous control outputs, isolated in pairs, common return for each pair. "ON" condition is electrically energised. Software inversion selectable.

Supports three types of outputs
continuous, pulsed and pulsed paired.

Pulsed operation
Software configurable in 0.05sec increments up to 12 seconds

Contact rating
5A @ 24VDC / 250VAC AC1

Isolation
Electromechanical relay

Analog Input Module

Differential voltage or current analog inputs, group isolated in four groups of four inputs each. Supports paired bipolar inputs.

Input range
0-10mA, 0-20mA/4-20mA, 0-5V individually jumper selectable.

Resolution
12 bit

Current shunt-
500 ohms (0 - 10mA)

Common mode rejection
- 100dB @ 50Hz

Pulse Input Module

Provides 8 individually isolated pulse count inputs. Supports pulse rate, pulse accumulation.

Input voltage range
12-24 VDC or 110-120VDC selectable.

Pulse rates
<55Hz

Serial I/O Module

Four individually isolated serial ports, software selectable for RS232 or RS485. Data rate 75 to 115200 bps asynchronous or synchronous.

Connectors
RS232 - RJ45
RS485 - 3 pin Phoenix Combi-con.

Data formats supported
Asynchronous or synchronous, HDLC/PPP

Protocols supported
DNP3.0, Modbus, Allen DF-1, Harris 6000, Cooper Bradley C2179, supports multidropped devices from each port.

Injection Controller Module

Supports all available channels for Zellweger Decabit, Plessey Rhythmic, Landis & Gyr Semagyr 50 injection codes. Highly and fully configurable plant interface.

Input range
12/24VDC

Contact rating
5A @ 24VDC / 250VAC AC1

Check input
supports three states for confirmation the injection telegram was successfully injected; no checkback, true checkback and inverted checkback.

Injection Display Module

Display and local control of individual lead channel status via thumb wheel selector

Time Sync Module

Output
IRIG-B, 1 pulse per second

All Modules

Connectors
Pluggable 2.5mm sq rising clamp connectors.

Input Power
18 -32 VDC

Open contact voltage
1KV RMS 1 minute (unless stated)

Insulation test voltage
2.5KV RMS 1 second, 2KV RMS 1 minute 5KVp BIL

Insulation rating
500V

Introducing

POWERCAT

Modular SCADA Remote Terminal Unit

Powercat is an industrial modular RTU designed specifically for Electrical Distribution and Telemetry applications. Powercat flexibly fits into existing SCADA systems with ease, collecting and concentrating data from Energy meters, Protection relays, Transformer relays, PLCs, PSUs and discrete I/O to return it to the SCADA Master or for internal program control.

- High I/O isolation
- Multiple protocol support
DNP3 Master and Slave, Modbus, DFI, Conitel and others
- PLC functionality
- GPS Time Synchronisation for RTU & protection relays onsite
- Local HMI/Config tools
- Ethernet interface TPC/IP
- Load Management System modules



New Zealand

Abbey Systems Ltd
L4, 220 Willis Street
PO Box 27 497
Wellington, New Zealand
Ph +64 4 385 6611
Fax +64 4 385 6848
Email sales@abbey.co.nz
www.abbey.co.nz

United States

Abbey Systems, Inc
965 Tyrnn St, Unit 7
Eugene, OR 97402, USA
Ph +1(541) 357 4386
Fax +1(541) 357 4386
Mobile +1(801) 699 3370
Email sales@abbey.com
www.abbey.com



BR-656-1.1-2012-May

INNOVATORS IN REMOTE CONTROL TECHNOLOGY



What's New

POWERCAT

Powercat is an update to our Powerlink RTU product with a new Architecture, faster M32c processor, Flash RAM and additional interfaces for Time Syncing and IP communications as standard.

Communications Controller Module

The hub of the system, the Comms Controller combines the functions of two of our earlier products, the communications controller and serial module into a single module. Four slots in the rear of the module allow users to fit interfaces for

- modems for radio or line comms for HDLC or Comitel
- Isolated RS-232/RS-485 serial card for Async protocols DNP3, Modbus, DF-1

In addition each module is fitted with

- IRIG-B Time Sync input
- Security Inputs (Tamper and Inhibit), Alarm Relay Output
- Config port for a Local Aspex HMI/Display or Local Master RTU setup
- Intermodule bus port to communicate with other I/O modules



Time Sync Module
IRIG-B and IPPs

Security/Alarm I/O

Intermodule Bus
to other I/O modules

Power
24VDC

Aspex HMI
Local Display and Control

Local Master
Configuration and program tool box

IP Communication
10/100-Base-T



2 x Spare Slots
For expansion

Serial Communications Port
RS232 or RS485

2w or Radio Modem
HDLC synchronous

Digital Input Module
40 paired isolated inputs for status monitoring. Debounce and Inversion are software selectable. LED display of each input status.

Analog Input Module
Connects analog transducers or inputs with 12 bit accuracy. Inputs are independently filtered for rejection of noise and ripple.

Serial I/O Module
Allows the connection of serial LEDs i.e. reclosers, feeder relays, generator relays, transformer VARs, flow meters, valve actuators, PLCs, VSDs etc without the need to independently wire discrete I/O modules. Uses standard protocols (DNP3.0, Modbus, DF-1) and specialised protocols (Cooper 2179, Harris 8000 and others).

Injection Display Module
A specialised module that displays the status of each injection control (load channel and allows local control to shed /restore the channel.



Digital Output Module
40 paired relay outputs to connect with external equipment for Control (i.e. contactors, actuators and relays). Protection against operation during power up/down and defect states.

Pulse Input Module
Power and flow meters are connected to the Pulse Input module; output pulses provide calculated consumption and flow information at the Master. These can later be used in pre-formatted reports or spreadsheets.

Injection Controller Module
A specialised module for the control of ripple injection plant for load management purposes. All standard codes catered for incl Enemet Decabit, L&G Sermagy 50, Plessey Rhythmic, K22, (Pulsadis, Ricotonic, Telegy - Enemet's IP). Local load levelling can be achieved using RTU logic programming and load metering providing it comes back to Powercat.

Powercat Features

- Wide range of communications options with the SCADA Master 2W, 4W, Sync Radio, Async Data Radio, IP, Fibre Optic
- **Modular**
Any combination of DI, DO, AI, Serial IO, Time Sync & Load Control modules may be connected to custom build your substation interface. Modules use a flexible intermodule bus for comms with the Communications Controller.

High Isolation

- Inputs are isolated in pairs to withstand 2kV/1min or 5kVp BIL
- Relay Outputs are paired and share a common
- Serial ports are isolated to IEC 255-5
- Optional RS232 and RS485 Fibre Optic converters

Logic Programming Functionality

- Each Powercat RTU can operate as a programmable logic controller with programs either downloaded from the SCADA Master over the communications channel or loaded via the configuration port.
- Logic programs for Alarm conditioning, selective data storage, Local Load Management
- Preprocess data at the RTU as virtual I/O

- Programs can run at the SCADA Master or RTU allowing online program creation and testing

Ethernet Port

- Connect via IP standard 10/100-Base-T