

KB-1016 EU

Maximum Adhesion Sheetfed Gel Vehicle

Description

KB-1016 EU is formulated to give the unique combination of excellent adhesion and oxidative dry with surprisingly fast set speed. KB-1016EU is formulated with the hottest oxidative vegetable oils and a high-end resin system.

Performance Characteristics

- Excellent adhesion to all types of plastic, foilboard and metal tin plate.
- Faster set speed than most high solids systems for plastic.
- Excellent water balance and litho performance.
- Positive oxidative drying

Safety Datasheet

Available on request

| Specifications | | Values | Method of analysis |
|----------------|-------|-----------|--------------------|
| Tack | | 300-350 | 30°C - 100 m/min |
| Viscosity | dPa.s | 1000-1500 | 40°C - C&P 10s-1 |
| Non-Volatile | % | 98-100 | |

Notice:

The presented information is accurate to be the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.



www.csm.umicore.com

Umicore Specialty Materials Brugge NV

Kleine Pathoekeweg 82
8000 Brugge, Belgium

Tel.: +32 50 320 720
Info.USMB@eu.umicore.com
www.csm.umicore.com