

KB-406 EU

Mineral Oil Free Fast Setting Sheetfed Grinding Vehicle

Description

KB-406 EU is a high solids hard drying grinding vehicle with excellent pigment wetting and maximum pigment dispersion. It is an excellent choice for all paper, paperboard and nonporous substrates to promote positive dry and adhesion. KB-406 EU promotes high holdout, with excellent gloss and transfer properties.

Performance Characteristics

- Mineral Oil Free and Swiss Ordinance compliant
- Excellent pigment wetting
- High oxidative potential
- Excellent water balance and litho performance.
- Excellent gloss

Safety Datasheet

Available on request

Specifications		Values	Method of analysis
Tack		325-425	30°C - 100 m/min
Viscosity	dPa.s	350-550	25°C - C&P 10s-1

Notice:

The presented information is accurate to be the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.



www.csm.umicore.com

Umicore Specialty Materials Brugge NV

Kleine Pathoekeweg 82
8000 Brugge, Belgium

Tel.: +32 50 320 720
Info.USMB@eu.umicore.com
www.csm.umicore.com