

AOR-IP-UPS-SUP
AOR-IP Series UPS Supervisor

Description

Model **AOR-IP-UPS-SUP** automatically and continuously monitors the primary power source being supplied to the uninterruptible power supply (UPS) for the AOR-IP Supervisor and either an AOR-IP Command Unit or an AOR-IP Auxiliary Command Unit. If the primary power source becomes unavailable, a relay contact output is provided.

Features

- Supervises Model **AOR-IP-UPS-CU-4H** or Model **AOR-IP-UPS-CU-24H**
- Relay contact output provided if the primary power source becomes unavailable
- Internal red LED illuminates when the coil is energized—saving time when verifying and testing an installed system
- Powered by the primary power source via a pass-through on the uninterruptible power supply (UPS)



Specifications

Dimensions (W x D x H):	5.250 x 3.125 x 2.500 in. (130 x 79 x 63 mm)
Weight:	0.85 lbs. (0.39 kg)
Operating Temperature:	+32° F to +120° F (0° C to +49° C)
Relative Humidity:	0-93% non-condensing, non-freezing at +32° F
Construction:	Backbox: 18 gauge cold-rolled steel (CRS), plated with 1/2-inch conduit knockouts on the top and bottom Cover: Gray ABS (UL 94 V-0)
Voltage (Input):	120VAC or 230VAC
Power Consumption:	45mA
Relay Contact Type:	DPDT (Form C)
Relay Contact Voltage Rating:	120VAC or 230VAC
Relay Contact Current Rating:	Maximum 10.0A (NO:1/6HP, NC:1/8HP) at 120VAC Maximum 7.0A at 230VAC
Supported Wiring:	14-22 AWG, solid or stranded
Compliance:	UL 864
Warranty:	5-year limited warranty