ADVANCETIG 325AC/DC

INVERTER TIG WELDER

Featuring the latest IGBT and active PFC technology the ADVANCETIG 325AC/DC is reliable, easy to use and energy efficient. Designed tough with IP23 and high quality, overspecified components - this machine is made for rugged NZ workshops and onsite tasks.



- IGBT module inverter technology for smooth & stable output, increased reliability and high duty cycle
- Phase loss protection shuts machine down automatically if power supply phase loss occurs, preventing damage
- Optional integrated heavy duty industrial trolley available with optional integrated water cooler
- Industrial IP23 casing with front panel protection resists damage, moisture and corresion
- Microprocessor control system for superior and dynamic arc characteristics
- · Extreme stress tested in production up to 550V, ensuring rugged reliability
- Lift TIG and HF start modes gives versatility when welding around sensitive electronic equipment
- Electronic HF TIG arc ignition system, contamination free and easy arc starting with low EMF interference
- 2T/4T multi-level trigger control modes
- Dual digital display meters for accurate pre-setting and feedback of welding parameters and output
- Durable and reliable with high quality & over specified electronic components
- Intelligent protection system with temperature, voltage and current sensors for increased reliability and safety
- Designed to work with generator power supply with protection from power surges
- · Potententiometer torch/ foot pedal remote control
- All remote functions connect through single plug 12 pin connection
- Power source wind tunnel coolling construction helps protect against environmental contamination
- Quick connect inlet gas fitting
- Accessories include integrated trolley and water cooler, 3m earth lead with heavy duty earth clamp, 4m MMA lead with heavy duty twist lock electrode holder, Strata Professional PR018 water cooled 25ft TIG torch with thumbwheel remote control, 2 stage flowmeter, argon gas regulator, 4m gas hose, gas inlet quick connector and hose clamps.









GENERATOR



INVERTER

TECHNOLOGY





COOLER



400V 50HZ

ADVANCETIG 325AC/DC

| DIMENSIONS (LxWxH) | WEIGHT | INPUT POWER SUPPLY | INPUT POWER SUPPLY TOLERANCE | MAXIMUM INPUT CURRENT | GENERATOR CAPACITY | MMA, AC/DC TIG CURRENT OUTPUT | MMA O/C VOLTAGE | MMA /AC TIG/ DC TIG DUTY CYCLE | TIG UP SLOPE DOWN SLOPE ADJUSTMENT | TIG GAS POST FLOW/PRE-FLOW ADJUSTMENT | TIG PULSE Frequency |
|-----------------------|--------|-----------------------------|------------------------------------|--------------------------|-----------------------|-------------------------------------|--------------------|--------------------------------------|--|---|------------------------|
| 550 x 240 x 445mm | 26kg | 400V AC 32A 3 PH 50/60Hz | ±10%V | 32A | 22.5kVA | 10 - 320A | 74V | 320A@60% 250A@100% | 0-10s | 0-2/0-10s | 0.5 - 250Hz |

| TIG PULSE WIDTH RANGE | AC TIG WAVEFORM | AC FREQUENCY ADJUSTMENT | INSULATION CLASS | POWER EFFICIENCY | POWER FACTOR | STANDARDS | WARRANTY |
|--------------------------|---|-------------------------------|---------------------|---------------------|-----------------|--------------------|------------------------------------|
| 5 - 95% | Square wave Sine wave Triangular wave | 50-250Hz | IP23 | 85% | 0.75 | EN60974-1: 2012 | 36 months* with registration |

^{* 36} Month Warranty only with online registration of product - www.strata.co.nz

TIG WELDING ACCESSORIES & CONSUMABLES

Standard Collets



| CODE: | DESCRIPTION: |
|----------|-----------------------|
| TCB10N23 | 1.6mm Standard Collet |
| TCB10N24 | 2.4mm Standard Collet |
| TCB10N25 | 3.2mm Standard Collet |

Standard Collet Bodies



| TCB10N31 | 1.6mm Standard Collet Body |
|----------|----------------------------|
| TCB10N32 | 2.4mm Standard Collet Body |
| TCB10N28 | 3.2mm Standard Collet Body |

Standard Ceramic Cups



| TCC1046 | 1/2" Standard Ceramic Cup |
|----------|----------------------------|
| TCC10N47 | 7/16" Standard Ceramic Cup |
| TCC10N48 | 3/8" Standard Ceramic Cup |

Mild Steel TIG Rods

· ER70S-6 Grade.

| TR16MS-70S-6 | 1.6mm x 1m Mild Steel TIG Rods |
|--------------|--------------------------------|
| TR24MS-70S-6 | 2.4mm x 1m Mild Steel TIG Rods |
| TR32MS-70S-6 | 3.2mm x 1m Mild Steel TIG Rods |

Aluminium TIG Rods

5356 Grade

| TR16AL-5356 | 1.6mm x 1m Aluminium TIG Rods |
|-------------|-------------------------------|
| TR24AL-5356 | 2.4mm x 1m Aluminium TIG Rods |
| TR32AL-5356 | 3.2mm x 1m Aluminium TIG Rods |

Stainless Steel TIG Rods

316 Grade.

| TR16SS-316 | 1.6mm x 1m Stainless Steel TIG Rods |
|------------|-------------------------------------|
| TR24SS-316 | 2.4mm x 1m Stainless Steel TIG Rods |
| TR32SS-316 | 3.2mm x 1m Stainless Steel TIG Rods |

Industrial Welding Trolley

- Suitable for ADVANCETIG 205ACDC/325 and water cooling unit or industrial storage
- Super duty wheels and castors
- · Includes gas bottle chains and takes 'G' size gas bottles.

| 22108 Industria | I Welding Trolley - V2 |
|-----------------|------------------------|
|-----------------|------------------------|

Compact Welding Trolley

· Capable of holding 'G' size gas bottles.

| 17384 | Industrial Welding Trolley |
|-------|----------------------------|
| | |

| ACCESSORY: | EZITIG | EZITIG | ADVANCETIG | ADVANCETIG |
|-----------------------------|---------|----------|------------|------------|
| | 205DC | 205AC/DC | 205AC/DC | 325AC/DC |
| Arc | O | O | O | O |
| Leads | AAL3550 | AAL3550 | AAL3550 | 17849 |
| Earth | O | O | O | O |
| Leads | AEL3550 | AEL3550 | AEL3550 | 17848 |
| TIG | O | O | O | O |
| Torch | PR026 | PR026 | PR026 | PR018 |
| TIG Starter Kit | DCKIT | DCKIT | ACDCKIT | ACDCKIT |
| Foot Pedal (Electric) | - | 17401 | 17401 | 17401 |
| Foot Pedal (Wireless) | - | 17399 | 17399 | • 17399 |

Tungsten Electrodes



- · Zirconiated for use on aluminium
- · Thoriated for use on stainless and mild steel

| TT16-150 | 1.6mm x 150mm Thoriated Tungsten Electrodes |
|----------|---|
| TT24-150 | 2.4mm x 150mm Thoriated Tungsten Electrodes |
| TT32-150 | 3.2mm x 150mm Thoriated Tungsten Electrodes |
| TZ16-150 | 1.6mm x 150mm Zirconiated Tungsten Electrodes |
| TZ24-150 | 2.4mm x 150mm Zirconiated Tungsten Electrodes |
| TZ32-150 | 3.2mm x 150mm Zirconiated Tungsten Electrodes |

MMA Welding Electrodes



| HYU21675 | 2.6mm 6013 General Purpose Electrodes - 5kg |
|----------|---|
| HYU21676 | 3.2mm 6013 General Purpose Electrodes - 5kg |
| HYU21677 | 2.6mm 7018 Low Hydrogen Electrodes - 5kg |
| HYU21678 | 3.2mm 7018 Low Hydrogen Electrodes - 5kg |

Water Coolers

- Suitable for ADVANCETIG machines with a water cooled torch set up (not incl.)
- · Induction motor with safety pressure switch.

| 24331 | Water Cooler Unit 400V |
|-------|------------------------|
| | w/ Connection Cable |

Industrial Storage Unit

- Fits in industrial welding trolley (#22108)
- 620 x 420 x 290mm
- · Convenient storage for welding wire, electrodes, gloves and welding accessories.



