

PROLINE


professional welding supplies

PROMAX HD 10-300 Series Welding Positioner

The turning structure of worm and gear has the function of self-lock, and the worktable can be turned steplessly between 0-90°.

Table of the welding positoner has center through hole, which is convenient for the pipe to be clamped and positioned, and protect the gas when it goes through the internal pipe, so it will improve the accuracy and quality of welding.

Special design of anti-electromagnetic, which reduces the high frequency interference of TIG's welding, and can improve the welding quality effectively.



Model	HD-10	HD-30	HD-50	HD - 100	HD-200	HD-300
Power Input	AC220V 50HZ	AC220V 50HZ	AC220V 50HZ	AC220V 50HZ	AC220V 50HZ	AC220V 50HZ
Drive Motor	DC220V 20W	DC110V 60W	DC220V 90W	DC220V 120W	DC220V 150W	DC220V 200W
Rated Load	10Kg	30Kg	50Kg	100Kg	200Kg	300Kg
Diameter of Table	180mm	310mm	315mm	400mm	400mm	500mm
Height of Table	220mm	380mm	400mm	520mm	520mm	650mm
Tilting Angle	0-90°	0-90°	0-90°	0-90°	0-90°	0-90°
Rotate Speed	2-16r/min	1-15r/min	1-15r/min	0-7r/min	0-7r/min	0.2-2.5r/min
Center Hole Diameter	/	25mm	25/30/65mm	45/75/140mm	45/75/140mm	90/130mm
Net Weight	10Kg	28Kg	32Kg	70Kg	76Kg	102Kg
Applicable Chuck	KC-65/80	KD-125/200/300	KD-125/200/300	KD-200/300/400	KD-200/300/400	KD-300/400/500