

PROLINE
professional welding supplies



#PT1000 RADIANT DIESEL HEATER



THE INSTANT HEAT SOLUTION FOR GARAGES, WORKSHOPS, FARMS & CONSTRUCTION SITES

RADIANT HEATING SURFACE - Distributes heat up to 162m² and catalyzes emissions.

ULTRA PORTABLE with sturdy steel handle.

COOL TO THE TOUCH OPERATION - 1 inch thick ceramic combustion chamber keeps exterior cool.

SAFE & ECONOMICAL - Auto shut-off if flame is extinguished or in power interruption.
Only 2.9L fuel consumption per hour!

EASY-TO-USE - Fill with fuel, plug into approved power source and enjoy the warmth.

QUALITY CONSTRUCTION - Rugged steel body, heavy duty motor & operating components.

RELIABLE - Sure-fire ignition system for quick easy starting in the coldest weather conditions.

VALUE-ADDED FEATURES - Power on/off switch, error indicator light, built in thermostat, contractor grade fuel cap, rugged steel construction and more!



120^K
BTU

36^{KW}
HEAT

40^L
TANK

12^{HRS}
HEAT

288^{M²}
AREA

71^{DBA}
@1M

IMPORTANT NOTICE

- Not for use in residential living areas or in non-adequately ventilated enclosed spaces.
- Proper ventilation required during operation.
- Read and keep the Owner's Manual included.
- Follow all safety requirements and operating instructions.
- Check state and local codes for permitted uses.
- Must be plugged into an approved standard electrical outlet for operation.
- BTU output, operating times, & other product specifications may vary and are subject to change without notice.

Ph: 0800 699 353
www.prolinewelding.com