

TECHNICAL SPECIFICATIONS

Product	Item Number	Primary Voltage	Fuse Size	Weight (kg)	Dimensions HxWxD (mm)	Protection/ Insulation Class	Compliance
PowerCRAFT™ 210C	K69034-1	240 V/1/50-60Hz (± 10%)	15	23.8	436 x 320 x 550	IP21S/H	AS60974.1 IEC 60974-1
PowerCRAFT™ 250C	K69033-1	240 V/1/50-60Hz (± 10%)	15**	22.7	436 x 290 x 590	IP21S/H	AS60974.1 IEC 60974-1

**Limited Output

WELDING OUTPUT

Product	Mode	Current range	Rated output
PowerCRAFT™ 210C	Stick	10 - 200A	200A, 28V @ 25%
	TIG	10 - 200A	200A, 18V @ 25%
	MIG	10 - 210A	200A, 24.5V @ 25%
PowerCRAFT™ 250C	Stick	10 - 200A	200A, 28V @ 20%
	TIG	10 - 200A	200A, 18V @ 20%
	MIG	10 - 250A	250A, 26.5V @ 20%

* GENERATOR REQUIREMENTS

Product	Output	Output range	Peak Inrush	Frequency
PowerCRAFT™ 210C	10 > kVA	200-270 Volts	500 Volts	50-60Hz
PowerCRAFT™ 250C	11 kVA	200-270 Volts	380 Volts	50-60Hz