



TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE



MMA TIG DC SCRATCH



CE MARKING



1 PH 230V



EAC CERTIFICATION

Overview

TECHNOLOGY 238 XT CE/MPGE 230V ACX+CASE

cod. 816252

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, cellulosic, etc.




















Recommended for motorgenerators, this model grants high performance despite power supply instability, thanks to the MPGE multiprotections: control device of the wave form, filter against input peaks, stabilization of oscillations. Robust and impact resistant.

Features:

- compact and light
- 50 Ø dinse
- high welding current stability in spite of mains voltage fluctuations
- regulation of arc force and hot start according to the type of electrode in use
- anti-stick device
- thermostatic, overvoltage, undervoltage, overcurrent protections.

Complete with MMA welding accessories and aluminium carry case.

Technical data

 CODE	CODE 816252	 A_{MAX}	MAX ABSORBED CURRENT 39 A	 cosphi	POWER FACTOR (cosphi) 0,7
 V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	 A_{60%}	ABSORBED CURRENT AT 60% - MAX 20 A	 D	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
 F	MAINS FREQUENCY 50 / 60 Hz	 P_{MAX}	MAX ABSORBED POWER 6,3 kW	 IP	PROTECTION DEGREE IP23
 A_{MIN}	CURRENT RANGE 5 - 200 A	 P_{60%}	ABSORBED POWER AT 60% 3 kW	 W	DIMENSIONS 37,5 - 50 - 22 cm
 A_{MAX 40°C}	MAX CURRENT 200 A - 35 %	 P_{GEN}	MOTORGGENERATOR MINIMUM POWER 10 kW	 kg	WEIGHT 10,55 kg
 A_{60% 40°C}	CURRENT AT 60% 140 A	 η	EFFICIENCY 87 %	 BAR CODE	EAN CODE 800489716580 6
 V₀	MAX NO LOAD VOLTAGE 80 V				

Included Accessories

CABLE

CABLE TW05V-A 1X025 L=02.00M DINSE



TOLEDO 300 WORK CLAMP



DALLAS 300 ELECTRODE HOLDER 300A