

TRANSTIG 200AC/DC

Portable Inverters



Specifications

Processes

Lift TIG, HF TIG (GTAW); Stick (MMAW)

Supply Voltage

240 volt, 1 phase, 50/60Hz

Current Range

5 – 200 amps (TIG)

Duty Cycle

20% @ 200 amps (GTAW, 40°C)

Recommended Generator

8.8 kVA for max. welding current

Power Source Weight

19kg

Dimensions

180 W x 360 H x 420 D mm

Features

- Compliant integrated Voltage Reduction Device
- Embedded micro-processor with digital controls
- Intelligent heat sensing fan operates on demand
- Easy to use digital display and panel control
- HF start TIG, Lift TIG & MMAW modes
- 2T, 4T with up/down slope and repeat function
- Intelligent self diagnostic control
- Save/Load (Recall) weld programs

Ordering Information

TRANSTIG 200AC/DC power source 700719

TRANSTIG 200AC/DC plant 700735

Power Source Contents

200AC/DC power source, 8 pin plug, 2 x 50mm dinse plugs, operating manual

Optional Accessories



Power Source Part No. 700719

The TRANSTIG 200AC/DC is a fully upgraded 240 volt, full digital control, AC/DC stick/Lift TIG, HF TIG Inverter power source. Featuring high frequency start, lift arc start, up/down slope, pulse on AC or DC, repeat (latch) function, DC pulse and spot mode, you've got the ultimate unit designed for precision TIG and MMAW of stainless steel and other DC weldable materials. Ideally suited for light fabrication and maintenance of aluminium and stainless steel.

Plant Contents

- TRANSTIG 200AC/DC power source
- 26 series TIG torch, 4m lead with remote current control
- 5m work lead
- 5m electrode holder
- COMET Argon regulator, 0-55 lpm 2 gauge
- Gas hose for TIG torch
- TIG accessory kit
- Plant storage and carry case
- Operation manual



Plant Part No. 700735