

TRANSTIG 300AC/DC

Portable Inverters



Specifications

Processes

Lift TIG, HF TIG (GTAW); Stick (MMAW)

Supply Voltage

415 volt, 3 phase, 50/60Hz

Current Range

5 – 300 amps

Duty Cycle

25% @ 300 amps (GTAW 40°C)

Recommended Generator

16 kVA for max. welding current

Power Source Weight

24kg

Dimensions

210 W x 420 H x 450 D mm

Features

- Compliant integrated Voltage Reduction Device
- Save/Load (Recall) weld programs
- Embedded micro-processor with digital controls
- Intelligent heat sensing fan operates on demand
- Easy to use digital display and panel control
- HF start TIG, Lift TIG & MMAW modes
- 2T, 4T with up/down slope and repeat function
- Intelligent self diagnostic control



Ordering Information

TRANSTIG 300AC/DC power source 700723

Power Source Contents

300AC/DC power source, 14 pin plug, 2 x 50mm dinse plugs, 5/8"-18 UNF gas connection, operating manual

The TRANSTIG 300AC/DC is a 415 volt, full digital control, AC/DC stick/Lift TIG, HF TIG power source. With features like high frequency start, lift arc start, up/down slope, welding program save/recall, pulse on AC or DC, repeat (latch) function and spot mode, you've got the ultimate unit designed for precision TIG and MMAW of stainless steel and other DC weldable materials.

Please refer to specifications at rear of brochure for comprehensive information.