For use with Diesel & Biodiesel

FC-P30-UL-D & FC-P30A-UL-D





Designed for the professional automotive technician, this cart-style UL Listed steel diesel caddy is rigorously tested for leakage, rupture, stability, abuse and endurance. This easy-to-move caddy is also OSHA compliant with all safety guidelines for diesel handling and comes in two options - manual pump (FC-P30-UL-D) and air-operated pump (FC-P30A-UL-D).

Features include:

- 30-gallon capacity steel tank
- UL Listed and complies with OSHA guidelines
- Fill level gauge
- Internal filter system
- 4-way directional valve
- Heavy-duty locking rear wheels and locking front casters
- Ground wire and clamp
- 8' PVC suction/discharge hose with internal grounding wire
- Decal set for content identification





UL Listed Pump

This heavy-duty, UL Listed cast iron rotary pump with carbon vanes and Viton seals offers a two-way operation for siphoning or dispensing fuel. One gallon is delivered for every 12 revolutions on the pump handle.

SPECIFICATIONS:	FC-P30-UL-D	FC-P30A-UL-D
GALLONS	30-gallon	30-gallon
MATERIAL	STEEL	STEEL
Римр	TWO-WAY MANUAL	UL LISTED AIR OPERATED
WHEEL SIZE – FRONT	5" LOCKING SWIVEL CASTERS	5" LOCKING SWIVEL CASTERS
WHEEL SIZE - REAR	10" HEAVY-DUTY FIXED	1□" HEAVY-DUTY FIXED
FILTER	1 O MICRON	10 MICRON
DIMENSIONS	24" W x 30" L x 41" H	24" W x 30" L x 41" H
WEIGHT	165 LBS.	165 LBS.

151 SNYDER AVE. | BARBERTON,OH 44203 | TOLL-FREE: 800-433-0708 | FAX: 330-753-6419

