

# Aboveground Used Oil Storage Systems

AGS-180D, AGS-245D, AGS-285D & AGS-500D



## NOTABLE FEATURES

- UL Listed double-wall tank provides 110% secondary containment
- Meets UL 142 specifications and requirements of Uniform Fire Code and NFPA 30
- Workbench-style tanks in 180-, 285- and 500-gallon capacities
- Vertical-style tank in 245-gallon capacity
- UL Listed 1" air-operated diaphragm pump with 30 gpm capacity
- Automatic pump shut-off to prevent overfilling
- 3/4" x 10' suction hose with quick connect coupler
- 2" drop tube with camlock fitting and dust cover
- Air filter/regulator
- Easy-to-read level gauge
- Protective cover for pump and shut-off valve

Used oil evacuation, storage and transfer is safer, cleaner and faster with a pump-assist system. Ideal for new car dealers, tire and automotive service stores and dealers, heavy-duty fleet owners and operators and municipal garages.



**AGS-180D**



**AGS-245D**



**AGS-285D**



**AGS-500D**

Specifications	AGS-180D	AGS-245D	AGS-285D	AGS-500D
Style	Workbench	Vertical	Workbench	Workbench
Capacity	180 Gallons	245 Gallons	285 Gallons	500 Gallons
Dimensions	56"L x 28"W x 40"H	40"L x 37-1/2"W x 69"H	67"L x 31"W x 42"H	89"L x 49"W x 40"H
Weight	725 lbs.	885 lbs.	795 lbs.	1300 lbs.

