



AIR OPERATED Oil & Grease DELIVERY SYSTEMS

These professional, quality, air-operated Grease Delivery Systems come as a complete package and include all required equipment. Built for durable and reliable operation, these systems fit 35 lb., 120 lb. and 400 lb. grease containers and come with a 50:1 high-pressure pump, control handle, Z-swivel, drum cover, follower plate and an 8' outlet hose.

GREASE

MODEL No.	DELIVERY CONTAINER	WEIGHT
JDL-5	35 LBS.	22 LBS.
JDL-16	120 LBS.	27 LBS.
JDL-16C	SAME AS JDL-16 WITH ADDITIONAL CASTER BASE	
JDL-55	400 LBS.	35 LBS.

SPECIFICATIONS:

PRESSURE RATIO	50:1
AIR INLET PRESSURE	70 - 115 PSI
AIR INLET CONNECTION	1/4" NPT (FEMALE)
AIR MOTOR EFFECTIVE DIAMETER	2.4" (63MM)
MAX PRESSURE	5600 PSI
OUTLET CONNECTION	1/4" NPT (MALE)



MODEL No.	CONTAINER	PUMP	HOSE	DRUM COVER	CONTROL HANDLE	FOLLOWER PLATE	SWIVEL	WGT.
JDL-5	35 Lb.	JDL-3640	JDH-1014	JD-3565	JD-3560	JD-3570	JD-3840Z	22 LBS.
JDL16	120 LBS.	JDL-3650	JDH-1014	JD-3566	JD-3560	JD-3571	JD-3840Z	27 LBS.
JDL16C	120 LBS.	JDL-3650	JDH-1014	JD-3566	JD-3560	JD-3571	JD-3840Z	27 LBS.
JDL-55	400 Lbs.	JDL-3655	JDH-1014	JD-3567	JD-3560	JD-3572	JD-3840Z	35 LBS.

OIL

These Air-Operated Oil Delivery Systems come as a complete package with all required equipment. These systems fit 16- and 55-gallon drums and are ideal for motor oil, synthetic oil, hydraulic oil and ATF. Each system is powered by a 3:1 medium pressure pump, comes with a delivery gun, 10' delivery hose, and the 16-gallon system includes a drum cover.

SPECIFICATIONS:

PRESSURE RATIO	3:1
AIR INLET PRESSURE	70 - 115 PSI
AIR INLET CONNECTION	1/4" NPT (FEMALE)
AIR MOTOR EFFECTIVE DIAMETER	2.49" (63MM)
MAX PRESSURE	348 PSI
OUTLET CONNECTION	1/2" NPT (MALE)



MODEL No.	CONTAINER	PUMP	HOSE	DELIVERY GUN	COVER	WEIGHT
JDOL-16	16-GAL	JD-3610	JDM-3930	JD-3930	JD-3566A	26 LBS.
JDOL-55	55-GAL	JD-3615	JDM-1038	JD-3930	N/A	22 LBS.

151 SNYDER AVE. | BARBERTON, OH 44203 | TOLL-FREE: 800-4330708 | FAX: 330-753-6419

