



PROLINK

Wireless Intercom System

Perfect for...

- House of Worship
- College Production
- Broadcast Studios
- Event Coordination
- Football Coaches
- Theaters
- Musicals
- and more!




TECH SPECS

- Two channels with four users per channel
- Push to Talk or Always On mode
- Heavy duty 4-pin XLR connector for headsets
- Microphone gain adjustment knob
- Out of range LED indicator
- Rechargeable AA batteries included

FEATURES

- 500 ft. line of sight wireless communication
- A/B channel selection
- Unlimited number of listen only belt packs
- Choice of single, dual muff, or lightweight headset
- Batteries operate 10 - 12 hours on a single charge
- FCC license free



ProLink 500 Packages	
PRO-540	Includes one BP-500M, three BP-500R, choice of four headsets, one GC-500, and a sturdy cardboard carrying case
PRO-570	Includes two BP-500M, five BP-500R, choice of seven headsets, two GC-500, and a sturdy cardboard carrying case
System Components	
BP-500M	ProLink master belt pack
BP-500R	ProLink remote belt pack (1, 2, 3)
BP-500L	ProLink listen only belt pack
H-2000	Intercom headset - dual muff
H-2000S	Intercom headset - single muff
H-2000LT	Intercom headset - lightweight
GC-500	Gang charger for four belt packs

Technical Specifications	
BP-500 - ProLink Belt Pack	
Frequency Range	902 - 928 MHz
Modulation	FSK
Wireless Range	Duplex 500' (152.4 m) line of sight
Antenna	1/2 - wavelength dipole
Headset Connector	4-pin XLR male
Power Supply	9VDC, 1.2ADC
Battery Life	10 - 12 hours
Dimensions (HWD)	4" x 3.5" x 2" (10.2 x 8.9 x 5.1 cm)
Weight	1 lb / .5 kg (with batteries)
Warranty	2 years
H-2000/H-2000S - Dual Muff / Single Muff Headset	
Drivers	Dynamic, 40 mm
Impedance	300 ± 15%
Frequency Response	20 Hz - 20 KHz
SPL	91 dB ± 3 dB
Rated Power	> 40mW
Distortion	< 5%
Microphone	Dynamic, uni-directional, low impedance
Microphone Sensitivity	Referenced to 0 dB = 1V/μbar, 1kHz Min -85 dB / Typical -83 dB / Max -81 dB
Frequency Response	200 Hz - 12 Hz
Connector	4-pin XLR female
Weight	Dual: 1 lb / 0.5 Kg Single: 0.8 lb / 0.4 Kg
Warranty	2 years



(Features & Specifications Subject to Change Without Notice)

Designed and Assembled in the USA