

# RECIPROCATING SAWS

## SSW-110

### Super Saw FEATURES

- Low vibration is achieved by the special design of the double piston mechanism
- Adoption of piston rings minimised power loss and improved cutting efficiency
- Rear exhaust system
- Double lock safety lever
- 14, 18, 24 and 32T saw blades available



| Rated Air Pressure    | Air Consumption | Stroke Speed            | Cutting Capacity  | Stroke | Weight |
|-----------------------|-----------------|-------------------------|-------------------|--------|--------|
| 6 kgf/cm <sup>2</sup> | 10.24 cfm       | 7,000 min <sup>-1</sup> | 3mm in mild steel | 11mm   | 0.62kg |

# LOW VIBRATION & IMPROVED CUTTING SPEED IMPROVED

- Low vibration is achieved by the special design of double piston mechanism.
- NEW adoption of piston rings minimises power loss and improves cutting efficiency.

## FINISHING FILE

### SUPER-HAND PORTABLE PRECISION FINISHING

## SH-100A

### Super hand replaces work FEATURES

- Ultra-small and ultra-lightweight
- Quick-change tool points for different jobs
- Can work with steel, glass, brass, aluminium, wood and other materials silently
- Handles big jobs with speed and ease



| Rated Air Pressure   | Air Consumption | Stroke Speed | Stroke | Max. Shank Dia. of Points | Weight |
|----------------------|-----------------|--------------|--------|---------------------------|--------|
| 6kgf/cm <sup>2</sup> | 8.5 cfm         | 3,700 rpm    | 9mm    | 6.3mm                     | 1.1kg  |

## ASH-900

### Weight reduced by half FEATURES

- Cutting capacity 3mm in mild steel
- Low vibration & longer piston stroke improves cutting speed
- Rear exhaust system for chip-scattering free operation
- Double safety lock lever



| Rated Air Pressure   | Air Consumption | Stroke Speed | Stroke | Max. Shank Dia. of Points | Weight |
|----------------------|-----------------|--------------|--------|---------------------------|--------|
| 6kgf/cm <sup>2</sup> | 7.1 cfm         | 6,300 rpm    | 9mm    | 5.0mm                     | 0.5kg  |

## OPTIONAL ACCESSORIES

### TO SUIT SSW-110

#### 10 Piece Set -

|                  |                             |
|------------------|-----------------------------|
| Part No. TA9A005 | 32 Teeth per inch Saw Blade |
| Part No. TA9A011 | 24 Teeth per inch Saw Blade |
| Part No. TB00193 | 18 Teeth per inch Saw Blade |
| Part No. TB00192 | 14 Teeth per inch Saw Blade |

Blade length is 60mm



### TO SUIT SH-100A & ASH-900

#### 1 Piece -

|                  |                               |
|------------------|-------------------------------|
| Part No. TA91752 | Rubber Pad Ass'y for SH-100A  |
| Part No. TA94625 | Supporter Ass'y for SH-100A   |
| Part No. TB04319 | Sanding Pad Ass'y for ASH-900 |

#### 5 Piece Set -

|                    |   |
|--------------------|---|
| Part No. TP00700-0 | Rat Tail SF-10                                  |
| Part No. TP00701-0 | Triangular Taper File SF-11                     |
| Part No. TP00702-0 | Half Rounded File SF-12 (Rat Tail / Double Cut) |
| Part No. TP00703-0 | Flat Bastard File SF-13                         |

Supporting Ass'y for SH-100A



Rubber Pad Ass'y for SH-100A



Sanding Pad Ass'y for ASH-900

