

LOCKFORMER

since
1938

DUAL HEAD GORELOCKER

Lockformer's Dual Head Gorelocker is your quality, efficient and cost-effective solution to the production of elbows, reducers, end caps and off-sets. Lockformer's operator friendly Dual Head Gorelocker provides the power to fabricate quality standing seam fittings in-house.

On a single machine platform, the Dual Head Gorelocker offers the ability to flange/swage on one end, while simultaneously closing the seam at the other end. The Dual Head Gorelocker allows operators to modify controls when flanging/swaging, providing complete control of production speeds. After closing on the second station and creating a standing seam, the Dual Head Gorelocker delivers an airtight seal, eliminating the need for sealing or painting.

Using minimal power and floor space, the Dual Head Gorelocker handles a variety of materials and thicknesses – up to 16 gauge (1.5mm) – to produce standing rib diameters from 4" to 60" (100-1500mm) with included tooling and can produce standing rib diameters from 4" and 50"-60" with additional tooling.



**MESTEK
MACHINERY**
◆ a Mestek company



5480 6th Street SW
Cedar Rapids, IA 52404
319.364.9181
sales@mestekmachinery.com
mestekmachinery.com

DUAL HEAD GORELOCKER

CAPACITY

- 16 gauge

DIAMETER RANGE

- Included Tooling: 4" - 60"
- Additional Tooling required for 4" and 52" - 60"

SPEED

- N/A

LENGTH

- N/A

MOTOR/VOLTAGE

- 460V/3 Ph/60 Hz

DIMENSIONS/WEIGHT

- Length - 106"
- Width - 32"
- Height - 44"
- Weight - 2,310 lbs.




Reducer



Offset Fitting



*Galvanized
Steel Elbow*



End Caps