biofit.com | 800.597.0246

Eton (ET) Series

advantage: ergonomic design | use: clean room, static control/ESD, various workspaces

Eton Series chairs offer a number of options to configure the seating to meet your workspace and budget requirements. The wide seat and trapezoid backrest provide comfort and performance shift after shift. Available under the BioFit 2-Day Shipping Program. 13-year warranty.

- Cloth and vinyl upholstery styles available to match various workspace requirements.
- Ergonomic seat with four-way contouring and internal seat board bumperguard.
- Meets CAL 117 fire retardant standards. Treatment to meet CAL TB 133 available as an option (not available in California).
- Black powder-coated paint finish standard on metal parts.
- Pneumatics are available to provide low, medium and high seat height ranges to accommodate many task requirements.
- Durable and easy to clean all-welded tubular steel base with affixed footring.
- Dual-wheel non-marring polyurethane casters resist movement when the chair is unoccupied, enhancing workplace safety by inhibiting seating from rolling away.

from rolling away.

= 2-Day Shipping

ordering information | january 2020 Eton Series | Standard Components

18.5"W x 17"D x 3"T seat, 14.5"W x 9.5"H backrest with lumbar support and plastic protective panel, soft touch pneumatic seat height adjustment; fixed rearward 3.5° seat tilt; backrest tilt and backrest height adjustment, grade 2 upholstery

Models with tubular steel base

Shown here:

Eton Series

with S base

footring, high seat height range

featuring affixed

Model#	Seat-Hgt.	Compatibility
ETS-L-RC-T-XF-XA-06	Low, 18"-22"	Desk
ETS-M-RC-T-XF-XA-06	Medium, 21"-28"	Standard Bench
ETS-H-RC-T-XF-XA-06	High, 25"-32"	High Bench

Model#	Seat-Hgt.	Compatibility
ETA-L-RC-T-XF-XA-06	Low, 17"-22"	Desk
ETA-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench
ETA-H-RC-T-XF-XA-06	High, 22"-32"	High Bench

Models with reinforced com	posite base		
Model#	Seat-Hgt.	Compatibility	
ETR-L-RC-T-XF-XA-06	Low, 17"-22"	Desk	
ETR-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench	
ETR-H-RC-T-XF-XA-06	High, 22"-32"	High Bench	

Models with wide aluminum base

Model#	Seat-Hgt.	Compatibility	
ETW-L-RC-T-XF-XA-06	Low, 17"-22"	Desk	
ETW-M-RC-T-XF-XA-06	Medium, 19"-26"	Standard Bench	
ETW-H-RC-T-XF-XA-06	High, 22"-32"	High Bench	

Ask about special and custom orders.

WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.





• 23" diameter tubular steel (S style) base with 21" diameter affixed footring.



 25.6" diameter, highprofile cast aluminum (A style) base.



 25.6" diameter, high-profile reinforced composite (R style) base.



• 28.7" diameter, highprofile wide aluminum (W style) base.

optional comp Component	MFG Code	Description
Seat	A	Saddle-shaped, contoured, waterfall front, 21"W x 19"D x 3"T; call factory for pricing when selected with a performance package
Backrest	• M	Larger, ergonomic, 18"W x 19"H (provides upper & lower back support; available on models with a seat height up to 32"); call factory for pricing when selected with a performance package
Armrest	ARS	Height/width adjustable with self-skinned urethane pads (not available with ISO 3 or 4 performance packages)
	PSAS	Height adjustable with self-skinned urethane pads
Seat Control	● FFAC	Free float articulating, pneumatic seat- and backrest-height adjustment; seat and backrest tilt independently via separate levers, and can free float or lock into place, seat can tilt forward ISO 5 performance package configurations
	EXE	Executive tilt: pneumatic seat- and backrest-height adjustment; backrest tilt; seat and backrest swivel tilt in unison; tilt tension control knob and single lever seat tilt lock into any position (<i>available on models with seat height 26</i> " or less)
	ASC	Articulating Seat Control: Pneumatic seat- and backrest-height adjustment; seat and backrest tilt independently and lock into place with a single lever (only available on ISO 3 and ISO 4 clean room models without arms)
Footring • AFP	AFP	Adjustable height, 22" diameter, oval tube construction, solid polished cast aluminum spoke (recommended for medium and high height models with A, W or R bases, adjusts easily without knobs/levers; not available with low height models or S style base units)
	● ATF	Adjustable height, 20" diameter, cast aluminum (recommended for medium and high height models with A, W or R bases, not available with low height models or S style base units)
Glides	HG	2" high polyamide glides
Casters	RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models
	● RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (<i>standard with ESD</i> performance packages)
Miscellaneous	SW	Skid wrapping, net cost per pallet
	VU	Upholstered underwrap to match seat upholstery
	FM	Memory Foam

ho	ery

uprioratery	
MFG Code	Description
СОМ	Customer's own material
Grade 2	Comes standard on upholstered models unless otherwise noted
Grade 3	Grade 3 upholstery
Grade 4	Grade 4 upholstery
Grade 5	Grade 5 upholstery
C133	Special fire retardant upholsteries, foam or barriers (as needed to meet California Technical Bulletin 133 & Boston Fire Code; upholstery choices may be limited. Minimums of Grade 2/3 fabric or Grade 3 vinyl are offered); not available in California

norformono nookoroo

Category	Class	MFG Code	
ESD	-*	●K	
Clean Room	ISO 8**	ISO8	
	ISO 7**	ISO7	
	ISO 6	ISO6	
	ISO 5	ISO5	
	ISO 4*	ISO4	
	ISO 3*	ISO3	
Clean Room/ESD	ISO 8/ESD*	ISO8K	
	ISO 7/ESD*	ISO7K	
	ISO 6/ESD*	ISO6K	
	ISO 5/ESD*	ISO5K	
	ISO 4/ESD*	ISO4K	
	ISO 3/ESD*	ISO3K	
Standard black metal part finish	-	06	
Chrome-plated metal parts, chairs w/A, W, R base	-	● C	
Chrome-plated metal parts, chairs w/S base	-	• C	
*Not available with R style base. **Comes standard with black powder coat metal fi	nish.		



