

Traxx (TX) Series

advantage: durability | use: laboratory, clean room, static control/ESD, healthcare, industrial, education

Highlighted by an 14-gauge steel seat, stools in this series are designed to handle tough industrial settings yet can be configured for use in clean rooms.



Dedicated to Design.
Committed to Quality.



• 23" diameter tubular steel (S style) base with 21" diameter affixed footing.



• 25.6" diameter, high-profile cast aluminum (A style) base.



• 25.6" diameter, high-profile reinforced composite (R style) base.



• 28.7" diameter, high-profile wide aluminum (W style) base.



ordering information | january 2020

Traxx Series | Standard Components
13" dia., 14-gauge steel, soft touch pneumatic seat height adjustment

Models with tubular steel base

Model#	Seat-Hgt.	Compatibility
TXS-L-RC-S-XF-XA-06	Low, 15"-19"	Desk
TXS-M-RC-S-XF-XA-06	Medium, 18"-25"	Standard Bench
TXS-H-RC-S-XF-XA-06	High, 22"-29"	High Bench

Models with cast aluminum base

Model#	Seat-Hgt.	Compatibility
TXA-L-RC-S-XF-XA-06	Low, 14"-19"	Desk
TXA-M-RC-S-XF-XA-06	Medium, 16"-23"	Standard Bench
TXA-H-RC-S-XF-XA-06	High, 19"-29"	High Bench

Models with reinforced composite base

Model#	Seat-Hgt.	Compatibility
TXR-L-RC-S-XF-XA-06	Low, 14"-19"	Desk
TXR-M-RC-S-XF-XA-06	Medium, 16"-23"	Standard Bench
TXR-H-RC-S-XF-XA-06	High, 19"-29"	High Bench

Models with wide aluminum base

Model#	Seat-Hgt.	Compatibility
TXW-L-RC-S-XF-XA-06	Low, 14"-19"	Desk
TXW-M-RC-S-XF-XA-06	Medium, 16"-23"	Standard Bench
TXW-H-RC-S-XF-XA-06	High, 19"-29"	High Bench

Ask about special and custom orders.

optional components

Component	MFG Code	Description
Footring	AFP	Adjustable height, 22" diameter, oval tube construction on solid polished cast aluminum spoke (<i>recommended for medium and high height models with A, W or R bases, adjusts easily without knobs or levers; not available with low height models or units with S style base</i>)
	ATF	Adjustable height, 20" diameter, cast aluminum (<i>recommended for medium and high height models with A, W or R bases. Not available with low height models or S style base units</i>)
Glides	HG	2" high polyamide glides
Casters	RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models
	RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (<i>standard with ESD performance packages</i>)
Miscellaneous	SW	Skid wrapping; net cost per pallet

performance packages

Category	Class	MFG Code
ESD	—*	K
Clean Room	ISO 6	ISO6
	ISO 6 w/S base	ISO6
	ISO 5*	ISO5
	ISO 5 w/S base	ISO5
	ISO 4*	ISO4
	ISO 4 w/S base	ISO4
Clean Room/ESD	ISO 6/ESD*	ISO6K
	ISO 6/ESD w/S base	ISO6K
	ISO 5/ESD*	ISO5K
	ISO 5/ESD w/S base	ISO5K
	ISO 4/ESD*	ISO4K
	ISO 4/ESD w/S base	ISO4K
Chrome-plated metal parts, chairs w/A, W, R base	—	C
Chrome-plated metal parts, chairs w/S base	—	C

*Not available with R style base.



WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.