

OptiSeal® Products Energized Seals and Packing Systems



Precision. Engineered. Performance.

Proven Design

For over 30 years OptiSeal® systems have provided reliable, low friction seals for multiple industries. By using a variety of profiles and materials, we are able to customize design solutions to specifically address your individual applications and needs. From modeling to manufacturing, our industry-proven design formulas and standards ensure the best performance possible under the most challenging conditions.

Configurations



OptiSeal® Standard



OptiFace Seal



Opti-Oilseal

The basic design of the OptiSeal® system consists of a U-shaped jacket made from an inert thermoplastic. The addition of a metal spring or elastomer energizes the OptiSeal® to provide sealing at low system pressures. At higher system pressures, the seal becomes pressure-energized by the fluid media. This sealing combination ensures adequate sealing across the entire pressure range.

With diameters from .040" (1mm) to 110" (2.8m), and customizable heights, the OptiSeal® can be configured to fit in almost any hardware. Our broad portfolio of materials used for OptiSeal® designs allows for sealing a multitude of media, from inert to highly reactive and corrosive fluids.

Lip Profiles

Seal characteristics such as sealability, wear, and friction are affected by lip profile construction and design. In addition to the following standard forms, the lip profile can be customized for specific gland configurations and for service in highly abrasive environments.

Profile & Code	S	A	B	C	D	F	G	J
Reciprocating	Green							
Rotating	Green							
Static	Green							
Oscillating	Green							
High Sealability	Green							
Exclusion	Green							
Low Friction	Green							
Step Gland	Red	Green	Green	Green	Green	Green	Red	Green
<3/16" ID	Red	Red	Green	Red	Green	Red	Red	Red

OptiSeal® Types

- OptiSeal® Standard
- OptiVee
- OptiFace Seal
- Flanged
- Opti-OilSeal

The OptiSeal® system's ability to perform in extreme temperature, pressure, and media make it an ideal choice for critical service sealing. The design benefits of the OptiSeal® system provide robust assemblies for the most extreme conditions, such as:

- High-pressure ranges
- Broad temperature requirements
- Large extrusion gaps
- Static and dynamic applications
- Potential misalignment
- Rough surface finishes
- API 607 FireSafe valves
- Low emission requirements

Back-Ups

To prevent seal extrusion, an anti-extrusion device, or back-up ring, can be added. Constructed from stronger material, the back-up ring blocks extrusion paths, allowing for maximum seal life in high temperature and high pressure applications.

Types of Back-Up Rings

- Integral Back-Up Ring
- OptiBack
- Delta Back-Up

Profile & Type
Bi-Directional Sealing
Reciprocating
Rotary
Oscillating
Static
Cryo
High Pressure
Low Pressure
Stackable
Food Service
Available Lip Profiles
Can be used with

Packing Designs

OptiPak® assemblies are specifically designed for conditions requiring redundant sealing surfaces found in a broad range of applications—from high pressures, and temperature ranges to large extrusion gaps or rough surface finishes.

Standard OptiPak® System



Tested and qualified by customers to meet API-6A-PR2 standards, this configuration boasts a robust non-elastomeric design for use in liquid and gas applications, as well as valve stems on high-pressure valves and chokes.

Low-Emission OptiPak® System



The elastomeric composite V-Ring within this assembly provides enhanced sealability for low-emission performance. The positive seal and resilience provided by the V-Ring enhancement work in tandem with the PTFE shell to ensure low friction operation.

High-Temperature OptiPak® System



This composite assembly enables the OptiPak® system to function optimally in environments with extreme temperatures, such as those found in steam systems. A variation of the standard system, a flexible graphite female replaces the thermoplastic PEEK female. The 1100°F (537.8° C) thermal limit of the graphite seal maximizes its functionality, making it suitable for a broad range of applications, from firesafe valves to geothermal assemblies and rotating swivel joints.

Rough Surface OptiPak® System



For applications with rough surface finishes, a BL style V-Ring may be added to the OptiPak®. The BL style V-Ring is made from a homogeneous elastomer for superior sealability on rough gland surfaces.



Preferred Do Not Use

1 OptiSeal®	2 OptiFace	3 Flanged OptiSeal®	4 Opti-OilSeal	5 Pakring	6 Opti-Ipak®	7 OptiSeal® w/ Back-Up	8 OptiVee® w/ Nipple	9 OptiVee®	10 Flat Band Coil Spring	11 Food Service Filled	12 Integral Back-Up	13 Multi-Spring
All	B	All	B, D	All	All	All	All	All	A, B, D	All	All	All
5, 9-13	10-12	1, 11-13	11, 13	1, 9, 12, 13	1, 5-9	1, 2, 10, 11, 13	1, 5, 11, 13	1, 5, 11, 13	1, 2, 4, 9, 12	1-3, 10, 11, 13	1-3, 10, 11, 13	1, 3-5, 9, 11, 12



To learn how CDI Energy Products can improve performance in your operations, please visit our website at: CDIproducts.com

Or talk with our experts at your regional office.

In-depth Solutions

CDI Energy Products is a designer and manufacturer of custom plastic and elastomeric products, seals, and ancillary metal components. As part of the global group Fenner, our multiple locations enable us to partner with clients worldwide to produce unique, high-performance solutions for the energy industry.



DISCLAIMER: The descriptions, design and performance information, and recommended uses for the products described herein are based on our design and manufacturing experience, product testing in specific conditions, and industry standards. As such, this information is for general guidance only. Our products are accompanied with their own warranty which is given in writing at the time of sale.

Tuff Breed, CDI Energy Products, and Sintermesh are registered trademarks of CDI Energy Products, LLC.
Tefzel®, Delrin®, Vespel®, Viton® and Teflon® are registered trademarks of DuPont used under license by CDI Energy Products.
All other trademarks are property of their rightful owners.
All rights reserved. No part of this brochure may be duplicated unless under the express written consent of CDI Energy Products.